



Electric muffle furnaces “R-3 L” and “R-8 L” 1100 °C

FOR TEMPERATURES ADJUSTABLE UP TO 1100 °C.
MICROPROCESSOR CONTROL WITH TFT TOUCH SCREEN.
PRECISION ± 2 °C OF THE SET VALUE.
RESOLUTION: 1 DIGIT.

NEW

REGULATION
SYSTEM
B

USB

FEATURES

Metal external case with vent at the back of the unit.
Interior and door made of ceramic fibre, resistant and durable (No asbestos). Heater situated at the side and bottom of the chamber.
USB and RS-232 output.

CONTROL PANEL

General

Main switch.
TFT touch screen 4.3".
Clock calendar.
Two working modes, normal or programming.
SPA – FRE – ENG menu.
Self-test on starting.
Temperature control auto-tuning.
°C/°F selection.
Type K probe.

Normal mode

Set point temperature selection
Up ramp or no ramp.
Stability time from 1 min to 99h or continuous.

Programming mode

10 programs capacity.
6 segments per program.
Stability time in each segment from 1 min to 99h (or continuous in the last segment)
Up ramps between segments or no ramps
Daily - weekly On / Off programming.



Temperature ramps graph

Alarms

Network failure detection alarm.
Probe error detection alarm.
Over temperature and low temperature alarms.
Visual audible warning alarms.
Up to 100 alarms storage (date, start time, end time and alarm type).

Datalogging

Datalogging memory up to 15000 data.
Logging interval from 5 seconds to 30 min.
Data download via RS -232 or USB.
PC software for on-line registration (via RS-232).

MODEL	Part No.	Capacity litres	Height / Width / Depht (interior) cm	Height / Width / Depht (exterior) cm	Power W	Weight Kg
N-3	2000368	3	11.5 12.5 20	43 34 47	1700	18
N-8	2000369	8	13 20 30	51 44 56	1800	28

Supplied complete with a refractory ceramic tray as a base and support for material to be assayed.

ACCESSORIES FOR MUFFLE FURNACES

Adaptable only for "Select-Horn-TFT" furnaces Part No. 2000376 and 2000377
All accessories need to be fitted in the factory prior to delivery.



Exterior exhaust tube.

Located at the furnace back with a ventilator motor to extract gases and vapours.
With an 80 mm Ø hat adapter.
Gases and Vapours can be extracted outside through the connecting tube.
Power consumption: 30 W.
Part No. 2001477

COMPLEMENTS



Gloves Thermal “Kevlar 800”

Conforms to EN 388, EN407 and EN420 standards.
For use with temperatures up to 800 °C, Made from seamless terry knit, with double face fibres, high level of protection against heat and flame.
Length 36 cm, universal fit.
Part No. 5000042



Crucible tongs.

With thermally protected plastic coated handles. With bow, curved tips.
Part No. 1001590 Total length 220 mm.
Part No. 1001591 Total length 330 mm.



Crucibles made of zirconium Zr.
Crucibles made of pure nickel Ni.
Crucibles made of glazed porcelain.
Crucibles made of stainless steel.
Crucibles made of quartz.
(See page 182).